

PneuTorque®
PTS™ Series

Model	PTS™-52-500	PTS™-52-800	PTS™-72-1000	PTS™-72-1350	PTS™-72-2000	PTS™-80-2700	PTS™-92-4000	PTS™-92-4000	PTS™-119-6000	PTS™-119-7000
Part Number/s	180241.B06	180242.B06	180243.B06	180244.B08	180245.B08	180246.B08	180250.B08	180250.B12	180248.B12	180249.B12
Torque Range	N-m	100 - 500	160 - 800	200 - 1000	270 - 1350	400 - 2000	540 - 2700	800 - 4000	800 - 4000	1200 - 6000
	lbf-ft	74 - 370	118 - 590	147 - 738	200 - 1000	295 - 1475	398 - 1991	590 - 2950	590 - 2950	885 - 4425
Square Drive	¾"	¾"	¾"	1"	1"	1"	1"	1½"	1½"	1½"
Output Speed (rpm)	35.5	25.7	20.4	14.7	9.2	7.3	5.3	5.3	2.6	2.6
Dimensions (mm)	ØD	Ø52	Ø52	Ø72	Ø72	Ø72	Ø80	Ø92	Ø92	Ø119
	H1	30	30	30	30	30	30	30	30	30
	H2	243	243	243	243	243	243	243	243	243
	L	263	263	290	290	324	290	347	347	369
	R1	59	59	76	76	76	76	70	70	90
	R2 min.	71	71	124	124	124	124	125	125	162
	R2 max.	131	131	167	167	167	167	175	175	210
Tool Weight (kg)	4.2	4.2	6.24	6.24	6.6	6.15	8.95	8.95	12.52	12.52
Reaction Weight (kg)	0.85	0.85	1.4	1.4	1.4	1.4	2.5	2.5	3.8	3.8

